

# THE VENDERS

To increase the overall capacity and selections of the machines with the most value-for-money way the Vision E-S is the perfect solution, using the payment systems and programming from the main vending allows to offer to the public a widest range of products.

## Technical Characteristics

- Programmable temperature from 35.5 °F to 53.6° F with different temperature areas, three points temperature division inside the cabinet.
- Capacity of up to 8 fully adjustable trays and up to 10 channels each.
- FIFO system used to deliver products.
- Vend detection by photocells.
- Leds lightening system with on-off programming.
- Transparent area of 1100 x 714 mm
- Auto - self diagnostic control system.
- Flexible configuration. The easyFlex system allows the fast modification of the width and depth of the channel. No additional spare parts are needed to create a new configuration
- Programmable torque and speed of the motors.
- Power Supply: 110 V
- Maximum consumption 650w

## Dimensions and Weight

- Dimensions: 72H x 31.5W x 37D Inch
- Weight: 654lbs.

## Structure

- Robust construction with an anti-corrosive and ant oxidation coating material
- Security lock with 3 locking points
- Injected foam on all the cabinet, assures the best refrigeration using lower power consumption by the cooling unit.

## Cash-Credit Management

- On the main vending machine, models Vision or Coffeemar

## Programming and Management

- On the main vending machine, models Vision or Coffeemar

## Options

- With or without cooling unit.

## Vision ES Satellite Unit

